



PO Box 6026, East Brunswick, NJ 08816, USA
Tel: 732-257-5002 Fax: 732-257-5003 Email: info@ceramsource.com

MATERIALS SAFETY DATA SHEET

Ceramsource, Inc.
PO Box 6026
East Brunswick, NJ 08816

Prepared By: Technical Department
Telephone No: 732-257-5002
Date: 1/1/14

Section 1 – Product Name

Common Name: Resin Bonded Magnesia-Carbon Brick (With Carbon Black)
Intended Use: Refractory Material
Product Name: INMC-10B

Section 2 – Composition and Information on Hazardous Ingredients

Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV	Sec. 313
Magnesium Oxide	1309-48-4	60-100	5 mg/m ³ (Resp Frac)	10 mg/m ³ (As Fume)	No
Carbon Black	1333-86-4	0.5-1.5	3.5 mg/m ³	3.5 mg/m ³	No
Aluminum	7429-90-5	1-5	15 mg/m ³ (Total Dust)	10 mg/m ³ (Metal Dust)	No
Phenolic Resin	--	1-5	Not Established	Not Established	No
Graphite	7782-42-5	5-10	2.5 mg/m ³ (Resp Dust)	2.0 mg/m ³ (Resp Dust)	No

Notes: (1) The PEL and TLV values shown above are 8-hour time-weighted averages, unless otherwise specified. "Not Established" means that no PEL or TLV has been assigned.

Section 3 – Hazards Identification

Emergency Overview:

No unusual fire or spill hazard. Dusts may be irritating to skin, eyes and mucous membranes.

Primary Route(s) of Entry for Particulate:

Inhalation: Yes **Other:** No
Skin: Yes **Ingestion:** No

Potential Adverse Health Effects:

Acute: Eye: Dusts of this product may be irritating.
Skin: Dusts of this product may cause skin irritation.
Inhalation: Dusts of this product may be irritating to respiratory tract.
Chronic: Eye: Dusts of this product may cause reddening or swelling of the eye. Skin: Dusts of this product may cause a skin rash (dermatitis).
Inhalation: Prolonged or repeated inhalation of dust of this product may result in increased lung cancer.

Carcinogenicity: Carbon black has been classified by IARC as a Category 2B carcinogen (known animal carcinogen and possible human carcinogen). Also, see Section 11 for additional information.

Signs and Symptoms of Overexposure: Skin rash can result from handling. Coughing can result from overexposure to dust.

Medical Conditions Generally Aggravated by Exposure to Particles:



PO Box 6026, East Brunswick, NJ 08816, USA
Tel: 732-257-5002 Fax: 732-257-5003 Email: info@ceramsource.com

Pre-existing diseases or other conditions of the lungs, skin, eyes, and mucous membranes

Section 4- First Aid Measures

Eye Contact: Flush product from eyes using large amounts of water, if irritation continues seek medical attention.

Skin Contact: Wash product from skin using soap and water, if irritation continues seek medical attention.

Inhalation: If exposed to excessive levels of dust remove victim to fresh air. Seek medical attention if coughing or other symptoms persist.

Ingestion: As shipped, product is not likely to be ingested, but if it occurs, do not induce vomiting. Seek medical attention

Section 5 – Fire Fighting Measure

Flash Point: Not Applicable

Flammable Limits: Not Applicable

LEL: Not Applicable

UEL: Not Applicable

Auto ignition Temperature: Not Applicable

Extinguishing Media: As appropriate for surrounding fire.

Fire Fighting Instructions: As appropriate for surrounding fire.

Fire Fighting Equipment: Fire fighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus (SCBA) and full protective clothing (bunker gear) when fighting fires.

Hazardous Combustion Products: Product will not burn, but may generate hazardous combustion products (such as carbon monoxide or vapors of the constituents shown in Section 2) when subjected to fire conditions.

Flame Propagation or Burning Rate of Solid Material: Not Applicable

Flammability Classification (As defined by 29 CFR 1910.1200): Not Flammable

Section 6 – Accidental Release Measures

For brick products, spills are remedied by recovering and restacking the shapes. If dusts are generated during the spill, these should be collected by gently sweeping the material into a dust pan or collecting with a vacuum device. All personnel engaged in cleanup operations should adhere to the instructions outlined in section 8 for personal protection. Disposal of wastes from cleanup operations should be carried out in accordance to the guidelines outlined in Section 13



PO Box 6026, East Brunswick, NJ 08816, USA
Tel: 732-257-5002 Fax: 732-257-5003 Email: info@ceramsource.com

Section 7 – Handling and Storage

Handling: Avoid direct contact with product or dust from product by wearing protective clothing, using approved respiratory protection, and wearing gloves of the impermeable type.

Storage: The product should be stored in a dry location. Pallet protection such as shrink-wrap or stretch-wrap should be kept in place until the product is required for installation.

Section 8 – Exposure Control/Personal Protection

Engineering Controls: Process enclosures, local exhaust ventilation, or other engineering process controls may be necessary to keep any air contaminants associated with this product within their TLV's. This is particularly true if the user operation generates dust, vapors, or mist.

Respiratory Protection: Since this product is a proprietary mixture of unique ingredients, it does not have an established limit for airborne concentration (PEL or TLV), which workers can routinely be exposed to without suffering adverse health effects. This MSDS is prepared to alert customers and other users to the various components of the product and their relative quantity and toxicity in the product as provided. The user must review his/her own circumstances and then determine what is required to establish a respiratory protection program that meets OSHA 1910.134 requirements. If workplace conditions warrant respiratory protection, use MSHA/NIOSH approved units as listed in the current 29 CFR 1910.134 for the existing conditions. Some type of respiratory protection is recommended even for the best conditions.

Actual respirator selection

should be made after consultation with a competent health and safety professional.

Eye Protection: Industrial-type safety glasses offer some protection, goggles or full face-piece respirators offer more.

Protective Gloves: Use as needed to prevent direct skin contact.

Other Protective Clothing or Equipment: Wear clothing designed to limit direct exposure to product, or dust, vapors, or mist associated with product. If clothing becomes contaminated, it should be laundered before wearing again. Barrier skin creams may be applied to parts of the body not otherwise protected, if workers find this beneficial. Maintain good personal hygiene. Wash Hands thoroughly before eating or drinking.

Section 9 – Physical and Chemical Properties

Appearance: Brick shape/ Color Black	Vapor Pressure: Not Applicable
Odor: Resin Odor	Vapor Density: Not Applicable
Water solubility: Insoluble	pH: Not Determined
Density (H₂O=1): 2.6-2.9	Boiling Point: Not Applicable
% Volatile (By Weight @ 1800°F): <5%	Melting Point: Greater than 2500° F



PO Box 6026, East Brunswick, NJ 08816, USA
Tel: 732-257-5002 Fax: 732-257-5003 Email: info@ceramsource.com

Section 10 – Stability and Reactivity

Chemical Stability: This product is stable under normal and/or anticipated conditions for shipping, storage and installation.

Conditions to avoid: None

Incompatible Material: May react with strong acids, such as hydrofluoric acid. Avoid contact between product and strong oxidizers.

Hazardous Decomposition or Combustion Products: This product contains a synthetic resin which, upon application of heat, may release minute but detectable quantities of (1) toxic and

irritating fumes including formaldehyde and ammonia, and/or (2) toxic gases such as the “monoaromatics” which include phenol and benzene. This situation is most likely to occur where conditions favor incomplete combustion and poor air handling practices are followed

Hazardous Polymerization: Not Applicable

Section 11 – Toxicological Information

As shown in Section 2, this product contains a phenolic resin. The phenolic resin contains less than 1% free phenol after curing, which is part of the manufacturing process.

Curing is achieved by heating the product in the range 300-400 °F. This removes most of the volatile fraction of the resin. In addition to the free phenol, the cured resin contains a trace of formaldehyde (less than 0.1%). This product contains a minor amount of carbon black (CAS#

1333-86-4). The International Agency for Research on Cancer (IARC) published the Monograph Volume 65-Printing Processes and Printing Inks, Carbon Black and some Nitro Compounds on 4/12/96. This document changed the carcinogenic rating for carbon black from Category 3 (insufficient evidence to make a determination) to Category 2B (known animal carcinogen, possible human carcinogen). Incomplete combustion products: Both phenolic resin and the

carbon black may undergo incomplete combustion when high heat is first applied to this product. Certain chemical compounds produced by incomplete combustion, in combination with poor air handling practices, may result in TLVs (threshold limit values) being exceeded for specific air contaminants.



PO Box 6026, East Brunswick, NJ 08816, USA
 Tel: 732-257-5002 Fax: 732-257-5003 Email: info@ceramsource.com

	LD₅₀	CD₅₀
Magnesium Oxide	No Data	No Data
Carbon Black	No Data	No Data
Aluminum	No Data	No Data
Phenolic Resin	No Data	No Data
Graphite	12,600 mg/kg (oral-rat)	No Data
Target Organs		
Magnesium Oxide	Eyes and respiratory system.	
Carbon Black	Respiratory system and eyes.	
Aluminum	No Data	
Phenolic Resin	No Data	
Graphite	Respiratory system and cardiovascular system.	
Long Term Toxicity		
Magnesium Oxide	Not Available	
Carbon Black	Possible human carcinogen (IARC).	
Aluminum	Repeated or prolonged inhalation may cause	
Phenolic Resin	Not Available	
Graphite	Not Available	

Short Term Toxicity	
Magnesium Oxide	Not Available
Carbon Black	Mildly toxic by ingestion, inhalation, and skin contact.
Aluminum	No Data
Phenolic Resin	Not Available
Graphite	Irritant to eyes and mucous membranes

Section 12 – Ecological Information

Accident Release: No information has been developed regarding the ecotoxicity or environmental fate of this product

Section 13 – Disposal Considerations

Waste Disposal Method:

The as-manufactured refractory, or dust from this material, is not considered a hazardous waste as defined by 40 CFR 261. However, used product (and dusts generated during maintenance and tear-out operations) may be contaminated with other hazardous substances from the particular application (for example, metals). Therefore, appropriate waste analysis



PO Box 6026, East Brunswick, NJ 08816, USA

Tel: 732-257-5002 Fax: 732-257-5003 Email: info@ceramsource.com

may be necessary to determine proper disposal. Waste characterization and disposal/treatment methods should be determined by a qualified environmental professional in accordance with applicable federal, state, and local regulations.

Section 14 – Transport Information

DOT (Department of Transportation) Classification under 49 CFR 172.101: Not Regulated

UN (United Nations) Number: Not Applicable

NA (North American) Number: Not Applicable

Section 15 – Regulatory Information

INTERSOURCEUSA, Inc. considers this product to be hazardous as defined by the OSHA Hazardous Communications Standard (29 CFR 1910. 1200). Section 2 chemicals, which must be addressed, and the summary of regulatory and other lists upon which they appear are:

Ingredient	CAS Number	List (s)
Magnesium Oxide	1309-48-4	1,2,3,4
Carbon Black	1333-86-4	1,2,3,4
Aluminum	7429-90-5	1,2,3,4
Phenolic Resin	--	
Graphite	7782-42-5	1,2,3,4

The lists are as follows:

1. ACGIH TLV “Threshold Limit Values” (1997)
2. OSHA Air Contaminants - Permissible Exposure Limits (1989)
3. Canadian Domestic Substances List
4. EPA TSCA Chemical Inventory List (1992)

WHMIS Hazard Class (Canada): D-2A

SARA TITLE III:

Section 302 Extremely Hazardous Substances: None

Section 311/312 Hazardous Categories: Irritant

Section 313 Toxic Chemicals: See Section 2



PO Box 6026, East Brunswick, NJ 08816, USA

Tel: 732-257-5002 Fax: 732-257-5003 Email: info@ceramsource.com

Section 16 – Other Information

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein; however, CeramSource Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.