

# Ceramsource Inc. Ceramic Fiber Textiles

## Material Safety Data Sheet

### 1. PRODUCT NAME

**Trade Name:** TaoFibre® Textiles (Cloth, Braid, Rope, Tape, Sleeving)

**Product Name:** Aluminosilicate Fiber Textiles

**Common Name:** Ceramic Fiber, Aluminosilicate Refractory Fiber

**General Use:** High temperature insulation

**Product Series:** Cloth, Braid, Twisted Rope, Tape, Sleeving

Manufactured and supplied by:

Ceramsource Inc.

P.O. Box 6026

26 Kennedy Blvd, Suite B

East Brunswick, NJ 08816

Tel: 732-257-5002 Fax: 732-257-5003

### 2. COMPOSITION AND INGREDIENTS

<u>Ingredient Name</u>	<u>CAS Number</u>	<u>Percent</u>
Aluminosilicate fiber	142844-00-6	80 - 85
Filament fiberglass	65997-17-3	5 - 10
Rayon/cellulose fiber	61788-77-0	Approx. 10

### 3. HAZARDS IDENTIFICATION

**Warnings!** Dust from this product generated by handling may cause skin, eye, and respiratory tract irritation. Possible hazards depend on duration and level of exposure.

**Possible effects on health:** Prolonged and repeated inhalation of aluminosilicate dust may cause chronic effects on respiratory system such as bronchitis, asthma, and emphysema.

**Signs and symptoms of excessive exposure:**

***Eye contact:*** Physical irritation

***Skin contact:*** Physical irritation

***Ingestion:*** Temporary irritation to gastrointestinal tract

***Inhalation:*** Pulmonary dysfunction

**Hazard Classification:**

Although studies, involving occupationally exposed workers, have not identified any increased incidence of respiratory disease. Results from animal testing have been used as the basis for hazard classification.

The Seventh Annual Report on Carcinogens (1994), prepared by the National Toxicology Program (NTP), classified respirable RCF and glasswool as substances reasonably anticipated to be carcinogens.

The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals, but insufficient data in humans.

The State of California, pursuant to Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986, has listed "ceramic fibers (airborn fibers of respirable size)" as a material known to the State of California to cause cancer.

The Commission of the European Communities (DG XI) has classified RCF as substances which should be regarded as if they are carcinogenic to humans.

IARC has also classified respirable crystalline silica, a possible by-product of RCF devitrification following sustained high-temperature (>1800<sup>0</sup>F) use, as a substance known to be carcinogenic to humans (Group 1).

#### **4. FIRST AID**

**Eye contact:** Flush immediately with large amounts of water for at least 15 minutes. Do not rub eyes. Get medical help if irritation persists.

**Skin contact:** Do not rub or scratch affected skin. Wash affected area gently with soap and water. Skin cream or lotion can also help after washing.

**Ingestion:** Relocate affected individual to an environment of clean and fresh air. Drink plenty of water. Seek medical help if symptoms persist.

**Inhalation:** Remove affected individual to a dust free place. Seek medical help if irritation persists.

**Notes to Physicians:** Skin and respiratory effects are the result of mechanical irritation; fiber exposure does not result in allergic manifestations.

#### **5. FIRE FIGHTING MEASURES**

**NFPA Unusual Hazards:** None

**Flash Point:** None.

**Extinguishing Media:** Use proper extinguishing media for the surrounding fire.

**Unusual Fire and Explosion Hazards:** None.

**Fire Fighting Protective Equipment:** Wear full bunker gear including positive pressure self-contained breathing apparatus.

## 6. ACCIDENTAL RELEASE MEASURES

Avoid creating airborne dust. Maintain routine housecleaning procedures. Vacuum only with HEPA filtered equipment. If sweeping is necessary, use a dust suppressant and keep material in closed containers. Do not use compressed air for clean-up. Workers should wear gloves, goggles and approved respirator. Avoid clean-up procedures that could cause water pollution.

## 7. HANDLING AND STORAGE

**Handling:** Minimize use of power tools to handle the material. Use hand tools whenever possible. Frequently clean work area with HEPA filtered vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.

**Storage:** Store the material in factory container in a dry area. Keep container closed when not in use.

**Empty Containers:** Product packaging may contain residue. Do not reuse.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Exposure Guidelines:**

<u>Components</u>	<u>OSHA (PEL)</u>	<u>ACGIH (TLV)</u>	<u>Supplier</u>
Aluminosilicate fiber	Non-established	Non-established	0.5 fiber/cc 8-hr
Filament fiberglass	5 mg/m <sup>3</sup> PEL (resp. dust) 15 mg/m <sup>3</sup> PEL (total dust)	1 fiber/cc 5 mg/m <sup>3</sup> (inhalable particulate)	Non-established
Rayon/cellulose fiber	5 mg/m <sup>3</sup> PEL (resp. dust) 15 mg/m <sup>3</sup> PEL (total dust) as PNOR	10 mg/m <sup>3</sup> (total dust) TLV, as PNOC	Non-established

**Engineering controls:** Use engineering controls such as ventilation and dust collection devices to limit airborne fiber concentrations to the minimum attainable level.

**Protective clothing:** Workers should wear full body clothing, gloves, hat and eye protection when handling the material. Wash work clothes separately from normal clothing. Rinse washer after use. It is recommended workers do not take work clothing

out of the work area. If they must, they should vacuum their clothes with a HEPA filtered vacuum before leaving the work area.

**Eye protection:** Wear goggles / safety glasses with side-shields.

**Respiratory protection:** Other than or before availability of engineering controls to reduce airborne aluminosilicate dust below the PEL, workers should use good work practices together with respiratory protection. Before providing respirators to workers, employers should 1) monitor for airborne aluminosilicate dust concentrations using proper NIOSH analytical methods and select the respiratory protection according to the results of that monitoring, 2) have physician determine if the workers are able to wear respirators, 3) make training programs available to workers for respiratory protection. Use NIOSH/MSHA approved respirators, in accordance with OSHA Respiratory Protection Standard 29 CFR 1910.134 and 29 DFR 1926.103, for the particular hazard or airborne concentrations in the work place.

**Recommended Respiratory Protections (When Handling Aluminosilicate Fiber Products):**

<u>Dust Concentration</u>	<u>Recommended Respirator</u>
Up to PEL	Disposable dust/mist respirator
Up to 10 times PEL	Disposable dust/mist respirator (e.g. 3M 9900) or half-face, air-purifying respirator equipped with high efficiency particulate air (HEPA) filter cartridges (e.g. 3M 6000 Series)
Up to 50 times PEL	Full-face air-purifying respirator equipped with high-efficiency particulate air (HEPA) filter cartridges (e.g. 3M 7800 with 7255 filters) or powered with air-purifying respirator (PARR) equipped with HEPA filter cartridges (e.g. 3M W3265S with W3267 filters)
Over 50 times PEL	Full-face positive pressure supplied air respirator (e.g. 3M7800 with W9435 hose and W3196 regulator)

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** White and odorless.

**Chemical family:** Aluminosilicate fibers.

**Chemical Indexes:**  $Al_2O_3 + SiO_2 >97\%$

$Al_2O_3 >48\%$

$Fe_2O_3 <1.1\%$

**Boiling point:** Not applicable.

**Vapor pressure:** Not applicable

**Vapor density:** Not applicable

**Specific gravity range:** 2-2.7

**% Volatile:** Not applicable

**Water solubility (%):** Not applicable

**PH:** Not applicable

**Melting point:** 3200 °F.

#### **10. STABILITY AND REACTIVITY**

**Incompatibility:** Hydrofluoric acid, phosphoric acid, and concentrated alkali.

**Hazardous decomposition products:** None.

**Hazardous polymerization:** Not applicable.

#### **11. TOXICOLOGICAL INFORMATION**

Epidemiological studies conducted by Institution of Human Environment Protection in China has provided no evidence that there is a direct cause-and-effect relationship between cumulative exposure to aluminosilicate fibers and lung cancers or particular pulmonary diseases.

However, recent toxicological experiments using physiological exposure method (inhalation) have produced findings of respiratory disease in rodents. Aluminosilicate refractory fiber has found to be a rodent carcinogen under the conditions that the rodents are exposed to high levels of the material (75 – 115 fibers/cc) on a basis of lifetime duration.

#### **12. ECOLOGICAL INFORMATION**

No data is available on adverse effects of the material on the environment.

#### **13. DISPOSAL CONCERNS**

This material is not classified as a hazardous waste under Federal regulations (40 CFR 261). It is the product users' responsibility to comply with local, regional, state or provincial regulations concerning specific requirements for disposal. Any processing, alteration or chemical additions to the material, as purchased, may make the information provided in this MSDS incomplete, inaccurate, or inappropriate. Original product boxes may contain material residue. Do not reuse them for other packaging purposes.

#### **14. TRANSPORT CONSIDERATIONS**

**U.S. Department of Transportation (DOT)**

**Bill of lading description:** Ceramic fiber textiles (49 CFR 172.202)

**Hazard class:** Not classified

**Labels:** Not applicable

**Placards:** Not applicable

**United Nations (UN) Number:** Not applicable

**North America (NA) Number:** Not applicable

## 15. REGULATORY INFORMATION

**CERCLA:** The aluminosilicate fibers of this product have an average diameter of 2-4  $\mu\text{m}$  and are not considered CERCLA hazardous substances (CERCLA 40 CFR 302).

**Clean Air Act (CAA):** Substances regulated as hazardous air pollution under Section 112 of the Clean Air Act Amendments of 1990:

Chemical Name

None

Most RCF products, including aluminosilicate fibers, are composed of RCF with an average diameter greater than 1 micron, and therefore are not considered hazardous air pollutants.

**SARA Title III:** This material does not contain substances reportable under Section 302, 304, 313 (40 CFR 372). Section 311 and 312 apply.

**TSCA:** All substances contained in this product are listed in the TSCA Chemical Inventory (Section 8b).

### State Regulations

#### California:

Substances listed by the State of California on Proposition 65, the Safe Drinking Water and Toxic Enforcement Act of 1986:

Chemical Name

Ceramic fibers (airborne particles of respirable size)

Glasswool fibers (airborne particles of respirable size)

CAS Number

142844-00-6

65997-17-3

#### New Jersey:

Chemicals which are listed as a special health hazard substances as defined in New Jersey Worker and Community Right to Know Act, New Jersey Administrative Code, Title 8, Department of Health, Chapter 59, Subchapter 10:

Chemical Name

NONE

CAS Number

#### Pennsylvania:

Chemicals which are listed as a special health hazard substance as defined in Pennsylvania Right-to-Know Law, Section 3800:

Chemical Name  
NONE

CAS Number

### International Regulations:

**Canadian Workplace Hazardous Material Information System (WHMIS)** categories apply to this material as follows:

Acutely Toxic: --	Biohazardous: --	Compressed Gas: --
Corrosive: --	Dangerously Reactive: --	Flammable/Combustible: --
Oxidizer: --	Other Toxic Effects: X	

### Canadian Environment Protection Act (CEPA):

All substances in this product are listed, as required, on the Domestic Substances List (DSL). Chemicals which are listed on the Non-Domestic Substances List:

<u>Chemical Name</u>	<u>CAS Number</u>
NONE	

## 16. OTHER INFORMATION

**Removal after Service:** Under sustained and steady high temperature over 1800 °F, this material will possibly transform to crystalline silica (cristobalite) in exposed portions. Prolonged or repeated exposure to respirable crystalline silica dust may lead to lung diseases. IARC has listed crystalline silica in Category 2A, a probable carcinogen ("Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans." IARC Monograph 68, June 1997, p. 210-211). The permissible exposure limit (PEL) set by OSHA for respirable cristobalite is 0.05 mg/m<sup>3</sup>. Whenever possible, follow Section 8 procedures for exposure controls and personal protection.

### Abbreviations:

CERCLA :	Comprehensive Environmental Response Compensation and Liability Act of 1980
CAS:	Chemical Abstracts Service
f/cc:	Fibers per cubic centimeter
HMIS:	Hazardous Material Information System
mg/m <sup>3</sup> :	Milligrams per cubic meter of air
NIOSH:	National Institute for Occupational Safety and Health
OSHA:	Occupational Safety and Health Administration
PEL:	Permissible Exposure Limit
SARA:	Super Amendments and Reauthorization Act
TSCA:	Toxic Substances Control Act

---

---

The above information is collected and prepared with reasonable care. However, Ceramsource Inc. makes no warranty, expressed or implied, as to the accuracy or suitability of the data herein above. Ceramsource Inc. assumes no responsibility for any damage or injury resulting from failure to follow the procedures recommended in this MSDS of using, handling, and storing the material.