



PO Box 6026, East Brunswick, NJ 08816, USA  
 Tel: 732-257-5002 Fax: 732-257-5003 Email: [info@ceramsource.com](mailto:info@ceramsource.com)

## MATERIALS SAFETY DATA SHEET

**Ceramsource, Inc.**  
**PO Box 6026**  
**East Brunswick, NJ 08816**

**Prepared By: Technical Department**  
**Telephone No: 732-257-5002**  
**Date: 1/1/14**

### *Section 1 – Product Name*

**Common Name: Rebonded Magnesia chrome bricks**  
**Intended Use: Refractory Material**  
**Product Name: INRBMCH-20A**

### *Section 2 – Composition and Information on Ingredients*

Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV	SEC 313
Magnesium Oxide	1309-48-4	40-70	5 mg/m <sup>3</sup> (Resp Frac)	10 mg/m <sup>3</sup> (As Fume)	No
Chromium (III) Oxide	1308-38-9	7-13	0.5 mg/m <sup>3</sup> (As Cr)	0.5 mg/m <sup>3</sup> (As Cr)	Yes
Iron Oxide	1309-37-1	7-13	10 mg/m <sup>3</sup> Dust (As Fe)	5 mg/m <sup>3</sup> Dust (As Fe)	No
Alumina	1344-28-1	5-10	15 mg/m <sup>3</sup> (Total Dust)	10 mg/m <sup>3</sup> (Total Dust)	No
Chrome Ore	1308-31-2	3-7	0.5 mg/m <sup>3</sup> (As Cr)	0.5 mg/m <sup>3</sup> (As Cr)	Yes
Zircon	14940-68-2	1-5	5 mg/m <sup>3</sup> (As Zirconium)	5 mg/m <sup>3</sup> (As Zirconium)	No

**Notes:** (1) The PEL and TLV values shown above are 8-hour time-weighted averages, unless otherwise specified. "Not Established" means that no FEL or TLV has been assigned.

### *Section 3 – Hazards Identification*

**EMERGENCY OVERVIEW**

No unusual fire or spill hazard. Dusts may be irritating to skin, eyes and mucous membranes.

**Primary Route(s) of Entry for Particulate:**

**Inhalation:** Yes  
**Skin:** Yes

**Other:** No  
**Ingestion:** No



PO Box 6026, East Brunswick, NJ 08816, USA  
Tel: 732-257-5002 Fax: 732-257-5003 Email: [info@ceramsource.com](mailto:info@ceramsource.com)

**Potential Adverse Health Effects:**

- Acute:** Eye: Dusts of this product may be irritating.  
Skin: Dusts of this product may cause skin irritation.  
Inhalation: Dusts of this product may be irritating to respiratory tract.
- Chronic:** Eye: Dusts of this product may cause reddening or swelling of the eye.  
Skin: Dusts of this product may cause a skin rash (dermatitis).  
Inhalation: Prolonged or repeated inhalation of dusts of this product in excess of the stated PEL or TLV may cause lung disease (pneumoconiosis).

**Carcinogenicity:** None of the ingredients in Section 2 are listed by IARC, NTP, or ACGIH as carcinogens or potential carcinogens.

**California Proposition 65:** This product contains crystalline silica, a chemical known to the State of California to cause cancer. This product contains chromite (Cr<sup>+3</sup>) which may in normal use, be converted chemically to a chromate (Cr<sup>+6</sup>) hexavalent chrome, a chemical known to the State of California to cause cancer.

**Radioactivity:** In common with many naturally occurring mineral products, Zircon contains very low levels of naturally occurring radioactive elements - principally uranium, thorium, and radium. The principal radiation hazard is due to inhalation of any dust, while a secondary lesser external hazard exists through gamma radiation. Zircon typically exhibits a total specific activity of 90-110 pCi/g.

**Signs and Symptoms of Overexposure:** Skin rash can result from handling. Coughing can result from overexposure to dust.

**Medical Conditions Generally Aggravated by Exposure to Particles:** Pre-existing diseases or other conditions of the lungs, skin, eyes, and membranes.

**Section 4- First Aid Measures**

**Eye Contact:** Flush product from eyes using large amounts of water. If irritation continues, seek medical attention.

**Skin Contact:** Wash product from skin using soap and water. If irritation continues, seek medical attention.

**Inhalation:** If exposed to excessive levels of dusts or vapors during heating, remove victim to fresh air. Seek medical attention if coughing or other symptoms persist.

**Ingestion:** As shipped, product not likely to be ingested; but if it occurs, do not induce vomiting. Seek medical attention.

**Section 5 – Fire Fighting Measure**

**Flash Point:** Not Applicable

**Flammable Limits:** Not Applicable

**LEL:** Not Applicable

**UEL:** Not Applicable

**Autoignition Temperature:** Not Applicable

**General Hazard:** Product is a refractory and will not burn.

**Extinguishing Media:** As appropriate for surrounding fire.

**Fire Fighting Instructions:** As appropriate for surrounding fire.

**Fire Fighting Equipment:** Fire fighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus (SCBA) and full protective clothing (bunker gear) when fighting fires.



PO Box 6026, East Brunswick, NJ 08816, USA  
Tel: 732-257-5002 Fax: 732-257-5003 Email: [info@ceramsource.com](mailto:info@ceramsource.com)

**Hazardous Combustion Products:** Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

**Flame Propagation or Burning Rate of Solid Material:** Not Applicable

**Flammability Classification (As defined by 29 CFR 1910.1200):** Not Flammable

### ***Section 6 – Accidental Release Measures***

For brick products, spills are remedied by recovering and re-stacking the shapes. If dusts are generated during the spill, these should be collected by gently sweeping the material into a dust pan or collecting with a vacuum device. All personnel engaged in cleanup operations should adhere to the instructions outlined in Section 8 for personal protection. Disposal of wastes from cleanup operations should be carried out in accordance with the guidelines outlined in Section 13

### ***Section 7 – Handling and Storage***

**Handling:** Avoid direct contact with product or dusts from product by wearing protective clothing, using approved respiratory protection, and wearing gloves of the impermeable type.

**Storage:** The product should be stored in a dry location and away from sources of heat (furnaces, boilers, incinerators, etc.). Pallet protection such as shrink-wrap or stretch-wrap should be kept in place until the product is required for installation.

### ***Section 8 – Exposure Control/Personal Protection***

**Engineering Controls:** Process enclosures, local exhaust ventilation, or other engineering process controls may be necessary to keep any air contaminants associated with this product within their TLV's. This is particularly true if user operation generates dust, vapor, or mist.

**Respiratory Protection:** Since this product is a proprietary mixture of unique ingredients, it does not have an established limit for airborne concentration (PEL or TLV), which workers can routinely be exposed to without suffering adverse health effects. This MSDS is prepared to alert customers and other users to the various components of the product and their relative quantity and toxicity in the product as it is provided. The user must review his/her own circumstances and then determine what is required to establish a respiratory protection program that meets OSHA 1910.134 requirements. If workplace conditions warrant respiratory protection, use MSHA/NIOSH approved units as listed in the current 29 CFR 1910.134 for the existing conditions. Some type of respiratory protection is recommended for even the best conditions. Actual respirator selection should be made after consultation with a competent health and safety professional.

**Eye Protection:** Industrial-type safety glasses offer some protection. Goggles or full face-piece respirators offer more.

**Protective Gloves:** As needed to prevent direct skin contact.

**Other Protective Clothing or Equipment:** Wear clothing designed to limit direct exposure to product or dusts, vapors, or mists associated with product. If clothing becomes contaminated, it should be laundered before wearing again. Barrier skin creams may be applied to parts of the body not otherwise protected, if workers find this beneficial. Maintain good personal hygiene. Wash hands thoroughly before eating or drinking.



PO Box 6026, East Brunswick, NJ 08816, USA  
 Tel: 732-257-5002 Fax: 732-257-5003 Email: [info@ceramsource.com](mailto:info@ceramsource.com)

**Section 9 – Physical and Chemical Properties**

<b>Appearance:</b> Brick/Shapes, Tan Color	<b>Vapor Pressure (mm Hg):</b> Not Applicable
<b>Odor:</b> None	<b>Vapor Density:</b> Not Applicable
<b>Water Solubility:</b> Insoluble	<b>PH:</b> Not Determined
<b>Density (H<sub>2</sub>O=1):</b> 2.8~3.3	<b>Boiling Point:</b> Not Applicable
<b>% Volatile (By Weight):</b> Nil	<b>Melting Point:</b> Greater than 2500F

**Section 10 – Stability and Reactivity**

**Chemical Stability:** This product is stable under normal and/or anticipated conditions for shipping, storage and installation.

**Conditions to Avoid:** None

**Incompatible Material:** May react with strong acids, such as hydrofluoric acid. Chromic oxide may react with alkali at high temperatures under oxidizing conditions.

**Hazardous Decomposition or Combustion Products:** None

**Hazardous Polymerization:** Not Applicable

**Section 11 – Toxicological Information**

	LD <sub>50</sub>	LC <sub>50</sub>
Magnesium Oxide	No Data	No Data
Chromium (III) Oxide	No Data	No Data
Iron Oxide	5500 mg/kg (ipr-rat)	No Data
Alumina	No Data	No Data
Chrome Ore	No Data	No Data
Zircon	No Data	No Data

Target Organs	
Magnesium Oxide	Eyes and respiratory system.
Chromium (III) Oxide	Eyes, skin and mucous membranes.
Iron Oxide	Respiratory system, lungs, eyes, and skin.
Alumina	Respiratory system.
Chrome Ore	Eyes, skin and mucous membranes.



PO Box 6026, East Brunswick, NJ 08816, USA

Tel: 732-257-5002 Fax: 732-257-5003 Email: [info@ceramsource.com](mailto:info@ceramsource.com)

Zircon Eyes, skin and mucous membranes.

Long Term Toxicity	
Magnesium Oxide	Not Available
Chromium (III) Oxide	Not classifiable as a carcinogen (ACGIH).
Iron Oxide	Not Available
Alumina	Not Available
Chrome Ore	Not classifiable as a carcinogen (ACGIH).
Zircon	Not classifiable as a carcinogen (ACGIH).

Short Term Toxicity	
Magnesium Oxide	Not Available
Chromium (III) Oxide	Irritant to skin, eyes and mucous membranes.
Iron Oxide	Not Available
Alumina	Irritant to skin, eyes and mucous membranes.
Chrome Ore	Irritant to skin, eyes and mucous membranes.
Zircon	Irritant to skin, eyes and mucous membranes.

### Section 12 – Ecological Information

**Accident Release:** No information has been developed regarding the ecotoxicity or environmental fate of this product

### Section 13 – Disposal Considerations

**Waste Disposal Method:** The as-manufactured refractory or dust from this material is not considered a hazardous waste as defined by 40 CFR 261. Wet material should be neutralized using Sodium Carbonate (or other acid neutralizing agent) then placed in container for disposal. However, used product (and dusts generated during maintenance and tear-out operations) may be contaminated with other hazardous substances from the particular application (for example, metals). Chromite (Cr<sup>+3</sup>) may in normal use, be converted chemically to a chromate (Cr<sup>+6</sup>). Hexavalent chromium (Cr<sup>+6</sup>) is considered a hazardous material. Therefore, appropriate waste analysis may be necessary to determine proper disposal. A qualified environmental professional in accordance with applicable federal, state, and local regulations should determine waste characterization and disposal/treatment method

### Section 14 – Transport Information

**DOT (Department of Transportation) Classification under 49 CFR 172.101:** Not Regulated  
**UN (United Nations) Number:** Not Applicable



PO Box 6026, East Brunswick, NJ 08816, USA  
Tel: 732-257-5002 Fax: 732-257-5003 Email: [info@ceramsource.com](mailto:info@ceramsource.com)

**NA (North American) Number:** Not Applicable

### **Section 15 – Regulatory Information**

INTERSOURCEUSA, Inc. considers this product to be hazardous as defined by the OSHA Hazardous Communications Standard (29 CFR 1910. 1200). Section 2 chemicals, which must be addressed, and the summary of regulatory and other lists upon which they appear are:

<b><u>Ingredient</u></b>	<b><u>CAS NUMBER</u></b>	<b><u>LIST(S)</u></b>
<b>Magnesium Oxide</b>	<b>1309-48-4</b>	<b>1, 2, 3, 4</b>
<b>Chromium (III) Oxide</b>	<b>1308-38-9</b>	<b>1, 2, 3, 4</b>
<b>Iron Oxide</b>	<b>1309-37-1</b>	<b>1, 2, 3, 4</b>
<b>Alumina</b>	<b>1344-28-1</b>	<b>1, 2, 3, 4</b>
<b>Chrome Ore</b>	<b>1308-31-2</b>	<b>1, 2, 3, 4</b>
<b>Zircon</b>	<b>14940-68-2</b>	<b>1, 2, 3, 4</b>

**The lists are as follows:**

1. ACGIH TLV “Threshold Limit Values” (1997)
2. OSHA Air Contaminants - Permissible Exposure Limits (1989)
3. Canadian Domestic Substances List
4. EPA TSCA Chemical Inventory List (1992)

**WHMIS Hazard Class (Canada):** D-2B

**SARA TITLE III:**

**Section 302 Extremely Hazardous Substances:** None

**Section 311/312 Hazardous Categories:** Irritant

**Section 313 Toxic Chemicals:** See Section 2

### **Section 16 – Other Information**

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein; however, Intersourceusa, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.